

Technical Datasheet - METYX Composite Reinforcements

PRODUCT CODE	5200.002.670
PRODUCT NAME	XM600/250
PRODUCT DESCRIPTION	
CUSTOMER CODE	
CUSTOMER ID	

REINFORCEMENT CONSTRUCTION		
LAYER	FIBER TYPE	AREA WEIGHT
1	Stitching	70 Tex
2	+45°	275 Tex
3	90°	68 Tex
4	0°	68 Tex
5	-45°	275 Tex
6	CSM	2400 Tex
7		
8		
9		

* Measurement method based on ISO 337.

TOTAL* **895** (±%3)

OTHER PORPerties		ROLL INFO	
Stitch Gauge	5 stitches/inch	Roll Width	127 cm
Stitch Type	Tricot	Roll Weight	91 kg
Stitch Length	2.6 mm	Roll Length	80 m
Pilot Yarn / Position	---	Core Diameter	3 inç (76.2cm) mm

Resin Compatibility	Loss on Ignition	Moisture Content
Polyester, Vinylester, Epoxy resins	Max.%0,70 by weight (ISO 1887)	Max.%0,20 by weight (ISO 3344)

Packaging	All rolls are wrapped with polyethylene bags; placed in pallet boxes or in single cardboard boxes or in pyramid style on pallets.
Labelling	Each roll is labelled on the inner side of the core, on the bag or on the cardboard boxes including a unique reference number for its traceability.
Storage	Store at %40-70 relative humidity and 18-30C temperature range. Recommended to be brought to working area 24 hrs prior to use.

System Certification	Product Certification
Metyx products are produced by Metyx USA INC. company who is run by ISO 9001 QA System.	DNV-GL Approved

METYX USA INC, 2504 Lowell Road, Gastonia, NC 28054
Phone : +1 704 824 **Fax :** +1 704 824 10 **Web :** www.metyx.com