

DESCRIPTION AND FIELDS OF APPLICATION:

Special filler reinforced with fibreglass. Easy sanding. Used to repair holes and other big imperfections of sheet metal and glass fibre panels.

Easy to sand.

VOC: <250 g/l 2004/42/IIb (b) (250) < 250



TECHNICAL DATA:

Composition	Unsaturated polyester resin, fibreglass and mineral charges
Flash point	> 32°C
Specific weight	1,55 ± 0,05
Available colours	Green
Safety data	See safety data sheet
Shelf life	18 months

SURFACE PREPARATION:



Iron, steel plates, glass fibre reinforced plastic.
Original paints or aged topcoat finishes.



Clean well the surface to be treated. Make sure it is dry and free from silicone, wax, grease and any extraneous material.
On base coats or enamel top coats, sand and clean the surface before applying the filler.

PROCESSING:



1-3 % paste hardener. Pot life 5-7' at 20° C.



Application with putty knife



< 30' at 20°C.



4-5' at 1 m.



P40-P80 roughing-out

TOOLS CLEANING:

With nitro or washing thinner.

CAUTIONS:

- Mix well the filler with 1-3 % hardener. Do not exceed with the hardener to avoid risk of staining during the painting operations.
- Do not use the product at temperatures below 5°C.
- Store in a cool and dry place.

DISTRIBUTOR:



RESINAS CASTRO S. L.

Pol. Ind. A Granxa, 3ª Paralela, C/ Cíes 190
36400 O Porriño - Pontevedra - España
Tlf.: 986 342 953 / Fax: 986 342 520
info@castrocomposites.com
www.castrocomposites.com

The technical information and instructions provided in this sheet are based on our own working experience. The company ensures the quality of the product. However, as the uses terms and conditions are out of our control, we decline any responsibility as the final result is concerned.