

ACMOS 82-2405

Releasing agent for UP/EP resins

PROPERTIES

Releasing agent in a spray bottle.
Appropriate for polyester, epoxy resins, PMMA and polyurethanes.
For mould manufacturing.

ADVANTAGES

Excellent mould release.
Free from CFC propellants.
Wide range of applications.
Economical use.

PROCESS

Shake thoroughly before using it.

The releasing agent should be pulverized over the mould from a distance of 20-30 cm. The pulverization must be thin and uniform.

If a better quality is required, the mould must be polished with a clean cloth.

STORAGE

Protect against cold and heat. The product must be at room temperature before being used.
Storage temperature: between 10° C and 30° C.
Life shelf: approximately 6 months in the original, sealed container.

responsibility of the user to determine the suitability of our products, under their own conditions before commencing with the proposed application. We guarantee the conformity of their products with their specifications but cannot guarantee the compatibility of a product with any particular application. We disclaim all responsibility for damage from any incident which results from the use of these products. Our responsibility is strictly limited to reimbursement or replacement of products which do not comply with the published specifications.

ACMOS CHEMIE KG
Industriestr. 37 + 49
Tel. (0421) 5189-0
Tfx. (0421) 511415

D-28199 Bremen
E-Mail: acmos@acmos.com
Homepage: www.acmos.com

SYNTHESAR, S.A.
Newton, 15
Tel: 0034 - 93 77 15 707
Fax: 0034 - 93 - 77 14 021

Pol. Ind. Sesrovires
E-Mail: comercial@synthesar.com
Homepage: www.acmos.com
E- 08635 SANT ESTEVE SESROVIRE

Additional information will be found in ACMOS EU security data sheet.

Our technical and commercial department are always at your disposition to answer technical questions.

08635 SANT ESTEVE SESROVIRE

All the provided information is based in our kThe information contained in this technical data sheet result from research and tests conducted in our Laboratories under precise conditions. It is the