

AIRTAC 2 LH

SPRAY ADHESIVE FOR TEMPORARY BONDING

■ DESCRIPTION

Airtac 2 LH is a spray adhesive designed for temporary bonding. Airtac 2 LH can be used to hold dry materials on contours and vertical surfaces. This product is ideally suited to resin infusion applications for holding plies, release films, peel plies, and infusion mesh in place until the vacuum bag is secured. Airtac 2 LH has a fine mist spray pattern.

■ BENEFITS

- Low hazard, fine mist adhesive.
- Excellent tack for faster vacuum bagging.
- More accurate material placement for infusion and better laminate quality.

■ TECHNICAL DATA

Characteristics	Methylene chloride free, toluene free
Shelf life	12 months from date of shipment when stored between 15 - 35°C

■ SIZES

Packaging Type	Content
12 cans per case	500 ml

■ APPLICATION

- Product can be applied to one or to both bonding surfaces. Ensure surfaces are clean and free of FOD, grease, oil, wax, etc. For best results surfaces should be between 10 – 30°C.
- Use with adequate ventilation. Shake aerosol well before use. Read SDS information and understand before use.
- Spray 15 – 25 cm away from the surface at 90° to the surface, applying an even coat. Allow the adhesive to tack off until there is no transfer when touched.
- Join surface and press firmly together.



■ NOTES

- Consult SDS prior to use. Do not store at temperatures over 50°C. Avoid exposure to sunlight. Do not store directly on concrete floor.
- Air Trigger sold separately.