

DESCRIPTION AND FIELDS OF APPLICATION:

Two-component filler containing high percentage of aluminium powder, which allows to obtain adhesion, hardness, resistance to water, fuels and lubricants. It has good anti-corrosive properties. It is mainly utilized to recover flaws of fusion, to restore and protect metal sheets, for filling imperfections on zinc-plated materials.

**TECHNICAL DATA:**

Composition	Unsaturated polyester resin and aluminium powder in different grain sizes
Specific weight	1,9 ± 0,1
Available colours	Dark grey
Safety data	See safety data sheet
Shelf life	18 months

SURFACE PREPARATION:

Zinc-plated sheet, aluminium and its alloys, iron, steel plate, plastics.
Original paints or aged topcoat finishes.



Clean well the surface to be treated. Make sure it is dry and free from silicone, wax, grease and any extraneous material.
On base coats or enamel top coats, sand and clean the surface before applying the filler.

CAUTIONS:

- Mix well the filler with 1-3 % paste hardener . Do not exceed with the hardener to avoid risk of staining during the painting operations.
- Do not use the product at temperatures below 5°C.
- Store in a cool and dry place.

PROCESSING:

1-3 % paste hardener
Pot life 3-6' at 20° C.



Application with putty knife



< 30' at 20° C.



4-5' at 1 m.



P80-P220

TOOLS CLEANING:

With nitro thinner.

DISTRIBUTOR:



RESINAS CASTRO S. L.

Pol. Ind. A Granxa, 3ª Paralela, C/ Cíes 190
36400 O Porriño - Pontevedra - España
Tlf.: 986 342 953 / Fax: 986 342 520
info@castrocomposites.com
www.castrocomposites.com

The technical information and instructions provided in this sheet are based on our own working experience. The company ensures the quality of the product. However, as the uses terms and conditions are out of our control, we decline any responsibility as the final result is concerned.