

DESCRIPTION:

Ultra-light polyester filler with a low specific weight and a creamy texture. VOC content under 250 g/l, limit of category of European legislation. Easy application by knife in order to obtain an exceptional smooth finish.



- Good adhesion on zinc plated sheets and on steel.
- Exceptional drying, application and sanding.
- Very smooth finish.
- Resistance to 100°C without changes
- Applicable with all Car Repair System filler and surfacer.

SURFACES:

Galvanized sheets, aluminium and its alloys, iron, steel plates, fibreglass and original paints or aged topcoat finishes.

VOC

<250 g/l 2004/42/II B (b) (250) <250 g/l

PREPARATION AND PROCESSING:

Degrease and sand with P80-P120 abrasive.



1-3 %

Pot life 3-5' at 20° C.

Theoretical coverage *: 7,3 m²/l for 100 dry micras



Application with putty knife



< 30' at 20° C.



4-5' at 1 m



P80-P120 coarse sanding

P180-P220 finishing

RECOATING:

Two-component water-based filler and surfacer and/or solvent. Polyester filler.

SOLID CONTENT:

87-88 %

SPECIFIC WEIGHT:

1,30 +/- 0,05

COMPOSITION

Unsaturated polyester resin, pigments, mineral charges and solvents.

GUARANTEE PERIOD:

12 months when keep in the correct storage conditions.

SECURITY INFORMATION:

See safety data sheet.

CAUTIONS:

Do not utilize the product at temperatures below 5°C
Store in a cool and dry place

DISTRIBUTOR:



RESINAS CASTRO S. L.

Pol. Ind. A Granxa, 3ª Paralela, C/ Cíes 190
36400 O Porriño - Pontevedra - España
Tlf.: 986 342 953 / Fax: 986 342 520
info@castrocomposites.com
www.castrocomposites.com

The technical information and instructions provided in this sheet are based on our own working experience. The company ensures the quality of the product. However, as the uses terms and conditions are out of our control, we decline any responsibility as the final result is concerned.