

DESCRIPTION

FILL MULTISOFT SOFT is a fine body putty easy to work, characterized by good shaping properties in any required thickness. Suitable hardness of putty to hardness of paintwork and the smooth non-porous surface allows to use this product as filling and finishing putty. Designed for use on steel and glass-fibre reinforced plastics.



Manual / machine sanding dry. Easy to work also with homogenous surfaces even by applying thick coats. Does not fill the sanding paper. Deep imperfections are filled in a few coats.

TECHNICAL DATA

Voc content :	2004/42/II(b)(250) <250
Shelf-life:	12 months
Density:	1,9 g/cm ³
Colour:	beige


APPLICATION

The surface must be cleaned, dry, degreased and matted. Thoroughly mix putty and 2-3% of hardener by weight. Apply within 5 minutes at 20°C. Higher temperature can reduce the pot life and accelerates the drying time.

Note: Using too much hardener can lead to topcoat discoloration. It is not recommended to use putty below 15°C.



Cleaning



Hardener addition

Putty	100g
Hardener	2-3 g



Body filling

3' – 5'



Drying time

16' - 30'




Hand sanding / dry

P100 - P320



Machine sanding / dry P100 - P320



Store in cold place

APPLICATION



RESINAS CASTRO S. L.

Pol. Ind. A Granxa, 3ª Paralela, C/ Cíes 190
36400 O Porriño - Pontevedra - España
Tlf.: 986 342 953 / Fax: 986 342 520
info@castrocomposites.com
www.castrocomposites.com

The technical information and instructions provided in this sheet are based on our own working experience. The company ensures the quality of the product. However, as the uses terms and conditions are out of our control, we decline any responsibility as the final result is concerned.